

SCF

CONTAINER
SOLUTIONS

SCFU 897006 0
22K2

SCF

131 132

MAX. GROSS TARE 36000 KG 79365 LB
NET 3190 KG 7030 LB

ISO SIDE DISCHARGE TANK

ISO Side Discharge Tank

Full occupational health and safety compliance sets SCF's Side Discharge Tank apart, as the operator can remain on the ground to either ground load or discharge the unit.

Key Features

- Safest ISO tank currently in the Australian market
- Breathe Easy Safety indicator
- Available in capacities 21,000L - 29,000L
- Fully compliant with ISO, IMO and IMDG standards
- Integrated automatic air ventilation for discharge and load

Options

- Clean flow 4 inch discharge with ball valve for highly viscous cargoes
- SCF "Safety lock" integrated foot valve and airline option
- Customer co-branding

Details

Suitable for bulk transport and storage, this unique ISO tank can seamlessly integrate into any supply chain that may have been previously serviced by tankers.

Unlike traditional ISO tanks, the bottom discharge can be accessed from the side of the tank allowing the operator to load and discharge without mounting the trailer.

SCF's patent pending integrated foot valve and airline significantly reduces the risk of a tank implosion.

This model also comes equipped with SCF's patented airline indicator valve, which notifies the operator that the tank is open to atmosphere and operational.

Both insulated and non-insulated versions are available.

Specifications

ISO Side Discharge Tank
26,000L variant

Specifications may vary

Volume		External	
Litres	26,000	Length (mm)	6,058
m ³	26.0	Width (mm)	2,438
		Height (mm)	2,591

Weight

Tare (kg)	3,190
Payload (kg)	32,810
MGW (kg)	36,000



Top:
Easy lifting points

Middle Left:
Discharge valve closed

Middle Right:
Discharge valve open

Below:
Ladder, ISO frame and top access



SCFU 897006 0
22K2



131 132

MAX. GROSS TARE	36000 KG
	79365 LB
	3190 KG
	7030 LB
NET	32810 KG
	72335 LB

CAPACITY	26000 L
MAWP	4.0 BAR

